

PRODUCT PROFILE

EC100-5102-2

Swimming Pool Heat Exchanger

Introduction

The Bowman EC100-5102-2 is an extremely versatile heat exchanger which is suitable for use with both larger spas and hot tubs, or domestic swimming pools up to 3,200ft³ via a boiler heat source. It features 'Universal Fit' composite end covers, for easy installation into pool or spa pipework and a choice of either a titanium, cupro-nickel, or stainless steel tube core.

Typical Heat Transfer

Boiler heating – 150,000 Btu/h

Product Benefits

Proven – heats spas and hot tubs extremely fast, reducing energy costs

Easy to install – solvent weld end covers with thermostat pocket


Durability – salt water and mineral rich fresh water compatible

Simple to maintain – easy disassembly for routine maintenance

Titanium models – full 10 year warranty on titanium materials



Specification



All dimensions in inches

Type	Tube Material	Typical Pool Capacity		Maximum Pool Water Flow	Maximum Hot Water Temp	Max. Operating Pressure Pool Water	Max. Operating Pressure Hot Water	Weight
		ft ³	gal	USGPM	°F	psi	psi	lb
EC100-5102-2C	Cupro-nickel	2,900	22,000	45.0	230	87	87	10
EC100-5102-2S*	Stainless Steel	3,200	24,000	53.0	230	87	87	10
EC100-5102-2T	Titanium	3,200	24,000	53.0	230	87	87	9


*Not suitable for use on pools fitted with salt water chlorinators or salt water pools.

Water Flow

As the graphs and table below illustrate, providing the right water flow volume is vital to the performance of the heat exchanger. If the flow rate of either the hot water supply, or the pool water circuit is too low, the heat exchanger will not perform at its designed efficiency and will be unable to transfer all the available heat energy in to the pool water.

For more information please visit; <https://ej-bowman.com/knowledge-centre/why-doesn't-my-pool-heat-up-faster/>



Heat Transfer



Btu/h Heat Transfer - EC100-5102-2


Pool water flow 52.8 US gpm at 82°F

Hot Water	Temperature & Heat Transfer			
Flow rate (US GPM)	180°F Btu/h	158°F Btu/h	140°F Btu/h	113°F Btu/h
2.6	68900	52900	39600	20500
5.3	100300	76800	57700	29700
7.9	120400	92100	69300	35800
10.6	135500	103700	77800	40300
13.2	146700	112300	84300	43700
15.9	156300	119400	89700	46400




✓ Optimum heat transfer performance ✗ Reduced heat transfer performance

Installation




If an automatic dosing system is added, it must be installed after the heat exchanger on the return to the pool.



Universal Fit End Covers

The EC100-5102-2 is supplied with 'Universal Fit' composite end covers, designed for use with either 1.5" nominal pipe size (48mm O/D) or metric 50mm O/D pool pipework. The 'socket union' component enables either diameter to be accommodated, as shown on the adjacent cross section illustration.



EJ Bowman (Birmingham) Ltd

Chester Street, Birmingham B6 4AP, UK

Tel: +44 (0) 121 359 5401 Fax: +44 (0) 121 359 7495

Email: sales@ej-bowman.com www.ej-bowman.com



All material contained in this leaflet is the intellectual property of EJ Bowman (Birmingham) Ltd. It is protected under copyright and may not be reproduced without prior written consent from the company. EJ Bowman (Birmingham) Ltd reserve the right to change specifications at any time without prior notice.